

FeatherCoat

Safety Data Sheet (SDS)

SECTION 1: IDENTIFICATION

Product identifier: FeatherCoat

Recommended use: Cement-based quick-drying leveling mortar

Supplier identification:

Supplier: LevelCore Industries Pty Ltd
Address: 46 Buckingham Dr, Wangara WA 6065, Australia
Phone: 1800 717 398

Important: This SDS has been compiled from the product Technical Data Sheet information provided and standard SDS section structure. Full GHS classification and ingredient disclosure must be confirmed against the actual formulation and raw material SDSs before regulatory use.

SECTION 2: HAZARD(S) IDENTIFICATION

GHS classification: Not available from provided source documents.

Label elements: Not available from provided source documents.

Other hazards: Use standard industrial hygiene and avoid contact with eyes/skin. See Section 8.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture.

Ingredients: Ingredient and CAS information not provided in the supplied source document. Confirm composition from formulation and upstream SDSs.

SECTION 4: FIRST AID MEASURES

Inhalation: Move to fresh air. Get medical attention if symptoms persist.

Skin contact: Remove contaminated clothing and wash skin with soap and water.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing and seek medical advice if irritation persists.

Ingestion: Rinse mouth. Do not induce vomiting. Seek medical advice if unwell.

SECTION 5: FIRE-FIGHTING MEASURES

Use extinguishing media suitable for surrounding fire.

Firefighters should wear self-contained breathing apparatus and full protective equipment where required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Avoid contact with eyes/skin and avoid breathing mists/dusts.

Contain and collect spillage. Prevent entry into drains and waterways.

SECTION 7: HANDLING AND STORAGE

Shelf life (from TDS): 12 months in original unopened packaging when stored dry, ventilated, and protected from light at ~23°C and 50% relative humidity.

Store separately; avoid mixing with water, grease, and corrosive substances; handle with care to prevent package damage.

Seal immediately after opening to avoid moisture absorption and caking; use opened product within 48 hours (per TDS).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Use with adequate ventilation.

Personal protective equipment: Safety glasses/goggles, protective gloves, and suitable protective clothing as needed. If dust/mist is generated, use appropriate respiratory protection.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Powder (cement-based leveling mortar per supplied technical information).

Colour/Odour: Not available from provided source documents.

SECTION 10: STABILITY AND REACTIVITY

Stable under normal conditions of use and storage.

Avoid incompatible materials as identified by formulation (information not available in provided source documents).

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information not available from provided source documents.

May cause irritation if contacted with eyes/skin or if dust/mist is inhaled (general guidance).

SECTION 12: ECOLOGICAL INFORMATION

Ecological information not available from provided source documents.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with local/regional/national regulations.

SECTION 14: TRANSPORT INFORMATION

Transport information not available from provided source documents.

Transport in accordance with applicable regulations.

SECTION 15: REGULATORY INFORMATION

Regulatory information not available from provided source documents.

SECTION 16: OTHER INFORMATION

Prepared for LevelCore Industries Pty Ltd.

Revision: 1.0

Issue date: 2025-12-31